NSN 5905-00-897-5639

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-897-5639 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.9370 inches Pilot Length: 0.0310 inches **Undercut Diameter:** 1.9375 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.938 inches **Body Length:** 0.968 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Shaft End Play:** 0.006 inches

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-897-5639

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Clamp ring
Electrical Resistance Per Section:
100.0 percent, rated amperes c and better flooring
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
123.0 single section and 143.0 single section and 175.0 single section and 207.0 single section and 227.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+150.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 7th secondary quality
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
5 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Special Features:
Drive coupling on shaft
Terminal Type And Quantity:
12 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
File: