## NSN 5905-00-897-7072

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-897-7072 **Section Quantity:** 1 **Body Style:** Cylindrical tab/flange mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Mounting Hole Diameter:** 0.096 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.188 inches **Body Length:** 0.546 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 330.0 **Nonturn Device Radius:** 0.125 inches **Lateral Distance Between Mounting Hole Centers:** 0.875 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 330.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section

## NSN 5905-00-897-7072

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
54.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0