## NSN 5905-00-899-0271

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-899-0271

### Style Designator:  #### Style Designator:  #### Style Designator:  #### Style Designator:  #### Style Designator:  ###################################
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 45.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Incapsulated Teminal Type: Vire lead Reliability Indicator: Rot established Rody Diameter: 1.280 inches Rody Length: 1.810 inches Power Dissipation Rating In Watts: 1.250 free air Rityle Designator:
Resistance Tolerance In Percent: 0.100/+0.100 Imbient Tempurature In Deg Celsius At Full Rated Power: 25.0 Imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 45.0 Imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 45.0 Imbient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Imbient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Imbient Type: I
Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  45.0 Ambient Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0 Ambient Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0 Ambient Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0 Ambient Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0 Ambient Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0 Ambient Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0 Ambient Range Of Tempurature In Deg Celsius At Zero Percent Rated Power:  65.0/+145.0 Ambient Range Of Tempurature In Deg Celsius:  66.0
Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  45.0  Pempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  Inclosure Method:  Encapsulated  Perminal Type:  Wire lead  Reliability Indicator:  Rot established  Body Diameter:  2.280 inches  Body Length:  8.810 inches  Power Dissipation Rating In Watts:  8.250 free air  Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  45.0  fempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  inclosure Method:  incapsulated  ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  1.280 inches  Body Length:  1.810 inches  Power Dissipation Rating In Watts:  2.250 free air  Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  45.0  dempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  nclosure Method:  incapsulated  deminal Type:  Vire lead  Reliability Indicator:  Rot established  Body Diameter:  1.280 inches  Body Length:  1.810 inches  Power Dissipation Rating In Watts:  2.250 free air  Style Designator:
dempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Ferminal Type: Vire lead Reliability Indicator: Not established Rody Diameter: 1.280 inches Rody Length: 1.810 inches Rower Dissipation Rating In Watts: 1.250 free air Relyel Designator:
rempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  nclosure Method: Encapsulated Ferminal Type: Vire lead Reliability Indicator: Not established Body Diameter:  1.280 inches Body Length: 1.810 inches Power Dissipation Rating In Watts: 1.250 free air Style Designator:
65.0/+145.0 nclosure Method: Encapsulated Ferminal Type: Vire lead Reliability Indicator: Not established Rody Diameter: 0.280 inches Rody Length: 0.810 inches Power Dissipation Rating In Watts: 0.250 free air Relye Designator:
Inclosure Method: Encapsulated Ferminal Type: Vire lead Reliability Indicator: Not established Rody Diameter: D.280 inches Rody Length: D.810 inches Power Dissipation Rating In Watts: D.250 free air Relyle Designator:
Fincapsulated Ferminal Type: Vire lead Reliability Indicator: Not established Rody Diameter: 0.280 inches Rody Length: 0.810 inches Power Dissipation Rating In Watts: 0.250 free air Reliability Indicator: R
Vire lead Reliability Indicator: Not established Rody Diameter: 0.280 inches Rody Length: 0.810 inches Power Dissipation Rating In Watts: 0.250 free air Retyle Designator:
Vire lead Reliability Indicator: Not established Rody Diameter: 0.280 inches Rody Length: 0.810 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator:
Reliability Indicator: Not established Rody Diameter: 0.280 inches Rody Length: 0.810 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator:
Not established  Body Diameter:  2.280 inches  Body Length:  2.810 inches  Power Dissipation Rating In Watts:  2.250 free air  Style Designator:
Body Diameter:  2.280 inches  Body Length:  2.810 inches  Power Dissipation Rating In Watts:  2.250 free air  Style Designator:
2.280 inches  Body Length: 2.810 inches  Power Dissipation Rating In Watts: 2.250 free air  Style Designator:
Body Length:  0.810 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:
0.810 inches  Power Dissipation Rating In Watts: 0.250 free air Style Designator:
Power Dissipation Rating In Watts:  0.250 free air  Style Designator:
2.250 free air Style Designator:
Style Designator:
ixial terminal each end
AND CONTROL COOK ONE
est Data Document:
0001-2430958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Init Of Measure:
-
Demilitarization:
No
Filg:
A001a0