NSN 5905-00-899-1891

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-899-1891 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.358 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** Between 0.1245 inches and 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.571 inches **Overall Diameter:** 0.500 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 325.0 **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.157 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:**

Rear end

Mounting Method:

Standard bushing

NSN 5905-00-899-1891

Precision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Hermetically sealed
Electrical Resistance Per Section:
250.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
65.0 single section
Unpackaged Unit Weight:
0.25 ounces
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Terminal Type And Quantity:
2 solder stud and 1 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0