## NSN 5905-00-899-5868

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-899-5868

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.060 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.690 inches
Mounting Bushing Length:
0.380 inches
Body Length:
0.936 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.380 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
310.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

## NSN 5905-00-899-5868

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts: 2.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0