

View Online at https://aerobasegroup.com/nsn/5905-00-899-9330

Section Quantity: 1 **Overall Length:** Between 1.254 inches and 1.359 inches **Overall Height:** Between 0.280 inches and 0.374 inches **Overall Width:** Between 0.235 inches and 0.300 inches Mounting Hole Diameter: Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.036 inches and 0.077 inches Shaft Length: Between 0.100 inches and 0.140 inches **Body Length:** Between 1.218 inches and 1.282 inches **Body Width:** Between 0.235 inches and 0.300 inches **Body Height:** Between 0.280 inches and 0.374 inches Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: Between 6120.0 and 9720.0 Maximum Starting Torque: 8.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Any acceptable **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 50.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 6120.0 and 9720.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section



Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0