Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-899-9331

# Section Quantity:

1

Rectangular w/mounting holes/slots

### **Overall Length:**

**Body Style:** 

Between 1.254 inches and 1.359 inches

### **Overall Height:**

Between 0.280 inches and 0.374 inches

### **Overall Width:**

Between 0.235 inches and 0.300 inches

### Mounting Hole Diameter:

Between 0.088 inches and 0.098 inches

### Shaft Diameter:

Between 0.036 inches and 0.077 inches

### Shaft Length:

Between 0.100 inches and 0.140 inches

### Body Length:

Between 1.218 inches and 1.282 inches

### Body Width:

Between 0.235 inches and 0.300 inches

### **Body Height:**

Between 0.280 inches and 0.373 inches

### Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

## Maximum Starting Torque:

8.00 inch-ounces

## Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

## **Mounting Facility Quantity:**

2

### Terminal Location:

Rear end

### Mounting Method:

Unthreaded hole

### **Electrical Resistance Per Section:**

100.000 kilohms single section

## Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0



### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

#### **Actuator Travel Control Feature:**

Clutch

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

81349-milr22097-1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A002a0