

View Online at <https://aerobasegroup.com/nsn/5905-00-899-9331>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Overall Length:**

Between 1.254 inches and 1.359 inches

**Overall Height:**

Between 0.280 inches and 0.374 inches

**Overall Width:**

Between 0.235 inches and 0.300 inches

**Mounting Hole Diameter:**

Between 0.088 inches and 0.098 inches

**Shaft Diameter:**

Between 0.036 inches and 0.077 inches

**Shaft Length:**

Between 0.100 inches and 0.140 inches

**Body Length:**

Between 1.218 inches and 1.282 inches

**Body Width:**

Between 0.235 inches and 0.300 inches

**Body Height:**

Between 0.280 inches and 0.373 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 6120.0 and 9720.0

**Maximum Starting Torque:**

8.00 inch-ounces

**Lateral Distance Between Mounting Hole Centers:**

Between 0.995 inches and 1.005 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Electrical Resistance Per Section:**

100.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 6120.0 and 9720.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-250.0/+250.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.8 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Test Data Document:**

81349-milr22097-1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0