Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-900-0171

······
Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
Between 0.515 inches and 0.555 inches
Terminal Length:
0.172 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
0.372 inches
Mounting Hole Diameter:
0.075 inches
Shaft Diameter:
Between 0.058 inches and 0.098 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
0.500 inches
Body Width:
0.235 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7200.0 and 16200.0
Center To Center Distance Between Terminals:
0.500 inches
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
500.000 kilohms single section

NSN 5905-00-900-0171

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: Between 7200.0 and 16200.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -600.0/+600.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-22097/3 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0