

View Online at <https://aerobasegroup.com/nsn/5905-00-900-2040>

**Section Quantity:**

3

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.105 mils and 1.125 centimeters

**Shaft Diameter:**

Between 0.1245 inches and 0.1248 inches

**Shaft Length:**

Between 0.865 inches and 0.885 inches

**Mounting Bushing Length:**

Between 0.365 inches and 0.385 inches

**Body Length:**

Between 1.980 inches and 2.000 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

5.0 and 28.0

**Actuator Type:**

Single shaft

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

4.0 percent, rated amperes c and better

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 7th secondary at 10'30 oclock

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Switch Current Type And Rating In Amps:**

0.150 ac/dc

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

13 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0