

View Online at <https://aerobasegroup.com/nsn/5905-00-900-2040>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.105 mils and 1.125 centimeters

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

Between 0.865 inches and 0.885 inches

Mounting Bushing Length:

Between 0.365 inches and 0.385 inches

Body Length:

Between 1.980 inches and 2.000 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Switch Type:

Rotary

Switch Voltage Rating In Volts:

5.0 and 28.0

Actuator Type:

Single shaft

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

4.0 percent, rated amperes c and better

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary at 10'30 oclock

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Switch Current Type And Rating In Amps:

0.150 ac/dc

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

13 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0