NSN 5905-00-900-2066

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-900-2066 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.187 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.080 inches **Body Length:** 0.405 inches **Body Width:** 0.190 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 8280.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:**

8280.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-00-900-2066

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No