Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-900-5484

Section Quantity:

1

- Body Style: Rectangular w/mounting holes
- Reliability Indicator:
- Not established
- Terminal Length:
- 0.500 inches
- Mounting Hole Diameter:
- 0.078 inches
- Shaft Diameter:
- 0.083 inches
- Shaft Length:
- 0.030 inches
- Body Length:
- 0.500 inches
- **Body Width:**
- 0.220 inches
- Body Height:
- 0.500 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- **Center To Center Distance Between Terminals:**
- 0.200 inches
- Lateral Distance Between Mounting Hole Centers:
- 0.520 inches
- **Mounting Facility Quantity:**
- 2
- **Terminal Location:**
- Right adjacent side single row
- **Mounting Method:**
- Unthreaded hole
- **Electrical Resistance Per Section:**
- 50.0 kilohms single section
- Center To Center Distance Between Center Terminal And Outside Terminal:
- 0.100 inches
- Power Dissipation Rating Per Section In Watts:
- 0.5 free air single section
- **Resistance Tolerance Per Section In Percent:**
- -20.0/+20.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0