## NSN 5905-00-901-2818

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-901-2818

View Crimino at https://acrossacogresspicoris/ite/weecoo co con 2012	
Section Quantity:	
1	
Body Style:	
Rectangular w/mounting holes	
Reliability Indicator:	
Not established	
Terminal Length:	
6.000 inches	
Mounting Hole Diameter:	
0.090 inches	
Shaft Diameter:	
Between 0.058 inches and 0.098 inches	
Shaft Length:	
Between 0.025 inches and 0.045 inches	
Body Length:	
Between 0.490 inches and 0.510 inches	
Body Width:	
Between 0.182 inches and 0.197 inches	
Body Height:	
Between 0.490 inches and 0.510 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
Between 7200.0 and 16200.0	
Lateral Distance Between Mounting Hole Centers:	
Between 0.513 inches and 0.526 inches	
Mounting Facility Quantity:	
2	
Terminal Location:	
Rear end	
Mounting Method: Unthreaded hole	
Electrical Resistance Per Section:	
50.000 ohms single section	
Rotary Actuator Travel In Angular Deg:	
Between 7200.0 and 16200.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent R	ated Power
150.0 single section	atou i owei.
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg	Celsius:
-50.0/+50.0 single section	Coloido.
55.5, . 55.5 dirigio 656iori	

## NSN 5905-00-901-2818

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-prf-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 wire lead
Specification Data:
81349-mil-prf-27208/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0

Mil-std (military Standard):

Mil-prf-27208 spec.