

View Online at <https://aerobasegroup.com/nsn/5905-00-901-2926>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

Between 3.710 inches and 3.910 inches

**Terminal Length:**

0.357 inches

**Body Diameter:**

Between 1.030 inches and 1.160 inches

**Shaft Diameter:**

0.251 inches

**Shaft Length:**

3.250 inches

**Mounting Bushing Length:**

Between 0.347 inches and 0.390 inches

**Body Length:**

Between 0.440 inches and 0.660 inches

**Overall Diameter:**

Between 1.452 inches and 1.517 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

Between 0.516 inches and 0.546 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Locking bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

500.000 kilohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0