NSN 5905-00-901-5273

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-901-5273

Out to Out to
Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Thread Length:
1.000 inches
Shaft Diameter:
0.1875 inches
Shaft Length:
1.250 inches
Body Length:
6.000 inches
Body Width:
1.000 inches
Body Height:
0.750 inches
Shaft Style:
Round, threaded
Actuator Type:
Single shaft
Longitudinal Actuator Travel:
3.985 inches
Longitudinal Actuator Effective Electrical Stroke Length:
1.320 inches
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
40.0
Mounting Facility Quantity:
4
Terminal Location:
Right-left adjacent sides
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
140.0 ohms single section

-0.50/+0.50 single section

NSN 5905-00-901-5273

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
160.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
4 tapped holes two ea on opposite sides spaced 5.500 in. C to c
Test Data Document:
77272-114es205-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig:

•

A002a0