NSN 5905-00-901-7048

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-901-7048

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0 Electrical Resistance: 1.300 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
1.300 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
25.0
Ambient Tempurature In Day Coloius At Zore Barent Bated Barren
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Not established
Body Diameter:
0.187 inches
Body Length:
0.560 inches
Power Dissipation Rating In Watts:
3.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0