## NSN 5905-00-901-7512

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-901-7512

View Online at https://aerobasegroup.com/nsn/5905-00-901-7512
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.900 inches
Body Diameter:
0.505 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.220 inches and 0.230 inches
Body Length:
Between 0.630 inches and 0.640 inches
Overall Diameter:
Between 0.555 inches and 0.565 inches
Shaft Style:
Round, slotted, undercut
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Maximum Starting Torque:
8.00 inch-ounces
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
4.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-5.00/+5.00 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 single section
Power Dissipation Rating Per Section In Watts:

1.0 free air single section

## NSN 5905-00-901-7512

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
50 degrees mech overtravel
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0