NSN 5905-00-901-7651

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-901-7651

Section Quantity:					
3					
Body Style:					
Cylindrical servo mounted					
Pilot Diameter:					
1.8750 inches					
Pilot Length:					
0.0600 inches					
Undercut Diameter:					
1.875 inches					
Undercut Width:					
0.0600 inches					
Body Diameter:					
2.000 inches					
Shaft Diameter:					
0.250 inches					
Shaft Length:					
1.000 inches					
Body Length:					
1.000 inches					
Mounting Lip Diameter:					
2.0000 inches					
Mounting Lip Depth:					
0.0600 inches					
Shaft Style:					
Round					
Actuator Type:					
Single shaft					
Mounting Facility Quantity:					
1					
Terminal Location:					
Lower adjacent side two rows					
Mounting Method:					
Shaft					
Electrical Resistance Per Section:					
50.000 percent, rated amperes c and better select					
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:					
150.0 all sections					
Power Dissipation Rating Per Section In Watts:					
2.0 7th secondary finish					
Fixed Tap Quantity Per Section:					
5 3rd section					

5 3rd section

NSN 5905-00-901-7651

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tan	Location	Tolerance	Per	Section:
ıap	LUCALIUII	I OIEI AIICE		Section.

-1.0/+1.0 ohms all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

Terminal Type And Quantity:

9 binding post

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A002a0