NSN 5905-00-902-0671

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-902-0671 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.268 inches First Flat Length: 0.380 inches Flat Height: 0.218 inches **Body Diameter:** 1.030 inches **Shaft Diameter:** Between 0.239 inches and 0.249 inches **Shaft Length:** 0.810 inches **Mounting Bushing Length:** 0.310 inches **Body Length:** 1.458 inches **Overall Diameter:** 1.064 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 3610.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 4.00 inch-ounces **Maximum Stop Torque:** 100.00 inch-ounces **Shaft End Play:** 0.005 inches

Shaft Runout: 0.002 inches

NSN 5905-00-902-0671

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
150.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section
105.0 single section
105.0 single section Power Dissipation Rating Per Section In Watts:
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section:
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature:
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section:
105.0 single section Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear
Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section
Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Precious Material And Location:
Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Precious Material And Location: Terminals gold
Power Dissipation Rating Per Section In Watts: 3.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -3.0/+3.0 single section Actuator Travel Control Feature: Clutch Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Precious Material And Location: Terminals gold Precious Material:

NSN 5905-00-902-0671

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf	f Life:		
N/a			
Unit Of Measure:			
_			

Demilitarization:

No

Fiig:

A002a0