NSN 5905-00-902-1220

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-902-1220

20.0420.0 Electrical Resistance: 7.100 kilohms 1 Resistance Tolerance in Percent: 4.0000/40.010 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Euli Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 485.0/4145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Langth: 0.340 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-9853 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) sheft Life: Na Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
7.100 kilohms Resistance Tolerance in Percent: -0.000/4-0.010 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: -65.0/+145.0 Inclosure Method: -67.0/+145.0 In	-20.0/+20.0
Resistance Tolerance In Percent: -0.000/+0.010 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.350 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Sylve Designator: Axial terminal each end Test Data Document: 94756-443-0963 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Na Unit Of Measure:	Electrical Resistance:
	7.100 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shell Life: Na Unit Of Measure: - Demilitarization: No Fig:	Resistance Tolerance In Percent:
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-9053 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	-0.000/+0.010
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Lingth: 0.250 inches Body Longth: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 fee air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Via Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: Demilitarization: No Filg:	145.0
Inclosure Method: Encapsulated Torminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	-65.0/+145.0
Terminal Type: Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-9553 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reactance Characteristic: Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Inductive Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reactance Characteristic:
Not established Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inductive
Body Diameter: 0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.250 inches Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
O.340 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.125 free air Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.340 inches
Style Designator: Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.125 free air
Test Data Document: 94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	94756-443-0953 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0