Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-902-1241

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Mounting Hole Diameter:

0.088 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.070 inches

Body Length:

1.250 inches

Body Width:

0.190 inches

Body Height:

0.320 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Center To Center Distance Between Terminals:

0.900 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal and unthreaded hole

Features Provided:

Humidity proof

Electrical Resistance Per Section:

500.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

7920.0



Center To Center Distance Between Center Terminal And Outside Terminal:
0.700 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0