Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-903-0624

Section Quantity:

1

Body Style: Cylindrical servo mounted Reliability Indicator:

Not established

Pilot Diameter:

Between 1.5610 inches and 1.5620 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Overall Length:

1.922 inches

Undercut Diameter:

1.625 inches

Undercut Width:

0.0730 inches

Body Diameter:

1.750 inches

Shaft Diameter:

Between 0.245 inches and 0.250 inches

Shaft Length:

Between 0.662 inches and 0.682 inches

Body Length:

1.250 inches

Overall Diameter:

1.938 inches

Mounting Lip Diameter:

Between 1.7450 inches and 1.7800 inches

Mounting Lip Depth:

Between 0.0880 inches and 0.0980 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

0.50 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches



Lateral Runout: 0.002 inches **Pilot Diameter Runout:** 0.002 inches Shaft Radial Play: 0.001 inches **Terminal Location:** Upper adjacent side two rows **Mounting Method:** Clamp ring **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -7.50/+7.50 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Test Data Document:** 10001-1855939 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 3 turret Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No

NSN 5905-00-903-0624

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

