Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-903-0774

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### First Flat Length:

0.375 inches

#### Flat Height:

0.216 inches

Body Diameter:

1.156 inches

#### Shaft Diameter:

0.250 inches

## Shaft Length:

## 0.656 inches

## Mounting Bushing Length:

0.281 inches

#### **Body Length:**

0.719 inches

#### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# **Mounting Method:**

Standard bushing w/shaft seal

# **Electrical Resistance Per Section:**

1.0 kilohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

## Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A002a0