NSN 5905-00-903-0775

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-903-0775 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.374 inches First Flat Length: 0.625 inches Flat Height: 0.216 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.656 inches **Mounting Bushing Length:** 0.281 inches **Body Length:** 0.718 inches **Overall Diameter:** 1.750 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces

Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches

NSN 5905-00-903-0775

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mechanical Backlash In Deg Angular Rotation:
1.5
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Panel seal and shaft seal
Electrical Resistance Per Section:
500.000 ohms single section
Rotary Actuator Travel In Angular Deg:
313.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+3.0 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section
and -2.0/+2.0 85 degrees celsius single section and +0.0/+4.5 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg: