NSN 5905-00-903-2429

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-903-2429

View Online at https://aerobasegroup.com
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.985 inches and 2.267 inches
Body Diameter:
Between 1.000 inches and 1.094 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 0.828 inches and 0.922 inches
Mounting Bushing Length:
Between 0.453 inches and 0.547 inches
Body Length:
Between 1.000 inches and 1.126 inches
Overall Diameter:
Between 1.000 inches and 1.094 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
6.00 inch-ounces
Maximum Stop Torque:
80.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
Between 0.235 inches and 0.265 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:

Locking bushing

NSN 5905-00-903-2429

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
8.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 290.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
6.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 tab, solder lug
Specification Data:
81349-mil-r-22/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: