## NSN 5905-00-903-2961



View	Online at https://aerobasegroup.com/nsn/5905-00-903-2961
Secti	ion Quantity:
1	
Body	Style:
Cylin	drical bushing mounted
Relia	bility Indicator:
Not e	established
Over	all Length:
Betw	een 0.937 inches and 1.187 inches
Body	Diameter:
Betw	een 1.032 inches and 1.156 inches
Shaf	t Diameter:
Betw	een 0.248 inches and 0.251 inches
Shaf	t Length:
Betw	een 0.469 inches and 0.531 inches
Mou	nting Bushing Length:
Betw	een 0.344 inches and 0.390 inches
Body	Length:
Betw	een 0.468 inches and 0.656 inches
Over	all Diameter:
1.515	5 inches
Shaf	t Style:
Roun	nd, slotted
Actu	ator Type:
Singl	e shaft
Maxi	mum Starting Torque:
6.00	inch-ounces
Maxi	mum Stop Torque:
128.0	00 inch-ounces

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-00-903-2961

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
3.5 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: