## NSN 5905-00-903-3014

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-903-3014 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.760 inches **Body Diameter:** Between 1.294 inches and 1.326 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.840 inches and 0.900 inches **Mounting Bushing Length:** Between 0.364 inches and 0.396 inches **Body Length:** Between 0.714 inches and 0.746 inches **Overall Diameter:** Between 1.324 inches and 1.356 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.544 inches and 0.576 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches **Shaft Radial Play:** 0.004 inches **Screw Thread Diameter:** 

**Screw Thread Series Designator:** Unef

0.375 inches

## NSN 5905-00-903-3014

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
350.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
Resistance Tolerance Per Section in Percent:
-5.0/+5.0 single section
-5.0/+5.0 single section
-5.0/+5.0 single section  Actuator Travel Control Feature:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Stops
-5.0/+5.0 single section  Actuator Travel Control Feature:  Stops  Tap Location From Ccw Terminal Per Section In Ohms:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Stops  Tap Location From Ccw Terminal Per Section In Ohms:  1000.0 single section
-5.0/+5.0 single section  Actuator Travel Control Feature:  Stops  Tap Location From Ccw Terminal Per Section In Ohms:  1000.0 single section  Function Characteristic Per Section:
-5.0/+5.0 single section  Actuator Travel Control Feature:  Stops  Tap Location From Ccw Terminal Per Section In Ohms:  1000.0 single section  Function Characteristic Per Section:  Single section linear
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section
-5.0/+5.0 single section  Actuator Travel Control Feature:  Stops  Tap Location From Ccw Terminal Per Section In Ohms:  1000.0 single section  Function Characteristic Per Section:  Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity:
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 4 turret
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 4 turret  Shelf Life:
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 4 turret  Shelf Life: N/a
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 4 turret  Shelf Life: N/a
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 4 turret  Shelf Life: N/a  Unit Of Measure:
-5.0/+5.0 single section  Actuator Travel Control Feature: Stops  Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 single section  Function Characteristic Per Section: Single section linear  Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -130.0/+130.0 single section  Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section  Terminal Type And Quantity: 4 turret  Shelf Life: N/a  Unit Of Measure: Demilitarization: