## NSN 5905-00-903-3823

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-903-3823

Electrical Resistance: 302.000 ohms Resistance Tolerance In Percent: 0.100/re-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/r445.0 Inclosure Method: Encapsulated Ferninal Type: Wire lead Reliability Indicator: Not established 300dy Diameter: 0.250 inches 300dy Langth: 0.312 inches 20125 free air Style Designator: Axial terminals one end Feste Data Document: 81549-mills3/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Wire Junit Of Measure: - Demilitarization: Uncertained of the Computer	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 0.1001/-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 0.250 inches 30dy Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 fee air Style Designator: xxixal terminals one end Fees Data Document: 91349-milr33/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Jiht Of Measure: — Demilitarization: No	-20.0/+20.0
Resistance Tolerance in Percent: 0.100/+0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/+145.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/+145.0 Fempurature Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 0.250 inches 30dy Length: 0.312 inches Power Dissipation Rating in Watts: 0.325 inches Power Dissipation Rating in Watts: 0.312 inches 10.325 year air 10.326 year air 10.326 year air 10.327 year air 10.328 year air 10.329 year	Electrical Resistance:
0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Vot established Body Diameter: 1,250 inches Body Length: 1,312 inches Power Dissipation Rating In Watts: 1,312 inches Power Dissipation Rating In Watts: 1,315 between the Comment of the Com	502.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Radiability Indicator:  Not established  Body Diameter:  10.250 inches  Body Length:  10.312 inches  Power Dissipation Rating In Watts:  10.125 free air  Style Designator:  Avail terminals one end  Test Dat Document:  1349-millr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Valuation of Measure:  - Demilitarization:  No.	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  Inclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Note established  Body Diameter:  10.250 inches  Body Length:  10.312 inches  Power Dissipation Rating In Watts:  10.125 free air  Style Designator:  Avial terminals one end  Fest Data Document:  8349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Sheff Life:  Via  Junit Of Measure:  — Demilitarization:  No	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4145.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Avail terminals one end  Test Data Document: 181349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  Via  Dirit Of Measure:  - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Interport of the property of t	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4145.0 nclosure Method: Encapsulated Ferminal Type: Write lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juint Of Measure: - Demilitarization: No Elig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-militg3/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: Demilitarization: No Filig:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: Bi31349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Jinit Of Measure: - Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminals one end Fest Data Document: B1349-milrs3/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: Via Juit Of Measure:	-65.0/+145.0
Ferminal Type:  Mire lead  Reliability Indicator:  Not established  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Avial terminals one end  Fest Data Document:  81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Unit Of Measure:  Demilitarization:  No  Fig:	Inclosure Method:
Are lead  Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Avial terminals one end  Fest Data Document: 81349-millr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Jinit Of Measure: - Demilitarization: No  Fig:	Encapsulated
Reliability Indicator: Not established  Body Diameter: 0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Avial terminals one end  Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Juit Of Measure: - Demilitarization: No  Pigg:	Terminal Type:
Note established  3ody Diameter:  10.250 inches  3ody Length:  10.312 inches  Power Dissipation Rating In Watts:  10.125 free air  Style Designator:  Avail terminals one end  Test Data Document:  18.349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Tig:	Wire lead
Body Length:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Avail terminals one end  Fest Data Document:  81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Signification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Reliability Indicator:
2.250 inches 3.30dy Length: 2.312 inches 2.312 inches 2.312 inches 2.312 inches 2.312 inches 2.313 inches 2.314 inches 2.315 free air 3.314 inches 3.315 Posignator: 3.314 inches 3.3149-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 3.3141 Shelf Life: 3.3142 Main and the state of the	Not established
Body Length:  0.312 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminals one end  Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Unit Of Measure:  Demilitarization:  No  Filg:	Body Diameter:
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	0.250 inches
Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminals one end  Fest Data Document:  0.1349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	Body Length:
D.125 free air  Style Designator:  Axial terminals one end  Fest Data Document:  B1349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	0.312 inches
Style Designator:  Axial terminals one end  Fest Data Document:  31349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Filig:	Power Dissipation Rating In Watts:
Axial terminals one end  Fest Data Document:  81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fiig:	0.125 free air
Fest Data Document:  81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formative excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	Style Designator:
31349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	Axial terminals one end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Filig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fiig:	81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a  Jnit Of Measure: - Demilitarization: No Filg:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a  Jnit Of Measure:   Demilitarization:  No  Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filg:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
\001a0	Fiig:
· · · · · ·	A001a0