

View Online at https://aerobasegroup.com/nsn/5905-00-903-5189

# Section Quantity:

1

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

#### Pilot Diameter:

0.62500 inches

#### **Pilot Length:**

Between 0.05700 inches and 0.06700 inches

#### **Overall Length:**

Between 1.907 inches and 1.989 inches

#### **Undercut Diameter:**

Between 0.870 inches and 0.880 inches

## Undercut Width:

0.78100 inches

#### **Body Diameter:**

Between 0.870 inches and 0.880 inches

#### Shaft Diameter:

0.125 inches

## Shaft Length:

Between 0.344 inches and 0.406 inches

## **Body Length:**

Between 1.563 inches and 1.583 inches

## Mounting Lip Diameter:

Between 0.87000 inches and 0.88000 inches

## Mounting Lip Depth:

Between 0.05700 inches and 0.06700 inches

## Shaft Style:

Round

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

## Maximum Starting Torque:

0.60 inch-ounces

## Maximum Running Torque:

0.50 inch-ounces

## Maximum Stop Torque:

128.00 inch-ounces

#### **Terminal Location:**

Upper adjacent side two rows



**Mounting Method:** Clamp ring **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Test Data Document:** 35351-737330-01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: Unit Of Measure: **Demilitarization:** A002a0

N/a

---

No Fiig: