NSN 5905-00-903-5191

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Not established **Overall Length:** 2.362 inches **Body Diameter:**

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-903-5191

2.410 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
Between 0.828 inches and 0.922 inches
Mounting Bushing Length:
Between 0.328 inches and 0.422 inches
Body Length:
1.440 inches
Overall Diameter:
3.205 inches
Shaft Style:
Round, slotted
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Maximum Starting Torque:
40.00 inch-ounces
Maximum Stop Torque:
240.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference

NSN 5905-00-903-5191

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method: Standard bushing Electrical Resistance Per Section: 35.0 ohms single section Rotary Actuator Travel In Angular Deg: Between 295.0 and 310.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section: A single section
Electrical Resistance Per Section: 35.0 ohms single section Rotary Actuator Travel In Angular Deg: Between 295.0 and 310.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
35.0 ohms single section Rotary Actuator Travel In Angular Deg: Between 295.0 and 310.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Rotary Actuator Travel In Angular Deg: Between 295.0 and 310.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Between 295.0 and 310.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
340.0 single section Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Power Dissipation Rating Per Section In Watts: 50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
50.0 heat sink single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
-10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section Standard Taper Curve Per Section:
25.0 single section Standard Taper Curve Per Section:
Standard Taper Curve Per Section:
·
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0