NSN 5905-00-903-5741

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-903-5741 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6240 inches and 0.6250 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Overall Length:** 1.660 inches **Undercut Diameter:** Between 0.624 inches and 0.625 inches **Undercut Width:** Between 0.0530 inches and 0.0730 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** Between 0.543 inches and 0.577 inches **Body Length:** 1.100 inches **Overall Diameter:** 1.046 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:**

maximum starting rorqu

0.40 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

NSN 5905-00-903-5741

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft End Play: |
|---|
| 0.0003 inches |
| Shaft Runout: |
| 0.002 inches |
| Lateral Runout: |
| 0.001 inches |
| Pilot Diameter Runout: |
| 0.001 inches |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Clamp ring |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 20.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 1080.0 |
| Function Conformity Tolerance Per Section: |
| -0.10/+0.10 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 105.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.5 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Denimalization. |

No

NSN 5905-00-903-5741

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0