## NSN 5905-00-903-5741

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-903-5741 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6240 inches and 0.6250 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Overall Length:** 1.660 inches **Undercut Diameter:** Between 0.624 inches and 0.625 inches **Undercut Width:** Between 0.0530 inches and 0.0730 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** Between 0.543 inches and 0.577 inches **Body Length:** 1.100 inches **Overall Diameter:** 1.046 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:** 

maximum starting rorqu

0.40 inch-ounces

**Maximum Running Torque:** 

0.30 inch-ounces

## NSN 5905-00-903-5741

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.0003 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
1080.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Denimalization.

No

## NSN 5905-00-903-5741

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0