NSN 5905-00-903-8034

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-903-8034

| Section Quantity: |
|--|
| 1 |
| Reliability Indicator: |
| Not established |
| Overall Height: |
| 0.359 inches |
| Overall Width: |
| 1.328 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.250 inches |
| Mounting Bushing Length: |
| 0.250 inches |
| Shaft Style: |
| Round, slotted |
| Shaft Bearing Type: |
| Bearing |
| Actuator Type: |
| Single shaft |
| Screw Thread Diameter: |
| 0.228 inches |
| Screw Thread Series Designator: |
| Uns |
| Screw Thready Qty Per Inch (tpi): |
| 28.0 |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 25.000 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| NI/a |

NSN 5905-00-903-8034

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0