

View Online at <https://aerobasegroup.com/nsn/5905-00-903-9096>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

Between 1.300 inches and 1.340 inches

Terminal Length:

Between 0.495 inches and 0.505 inches

Overall Height:

Between 0.310 inches and 0.330 inches

Overall Width:

Between 0.180 inches and 0.200 inches

Mounting Hole Diameter:

0.088 inches

Shaft Diameter:

Between 0.105 inches and 0.115 inches

Shaft Length:

Between 0.060 inches and 0.080 inches

Body Length:

Between 1.240 inches and 1.260 inches

Body Width:

Between 0.180 inches and 0.200 inches

Body Height:

0.320 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.890 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

100.0 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+300.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0