NSN 5905-00-903-9675

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-903-9675 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.5620 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.625 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 1.830 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.812 inches **Body Length:** 2.500 inches **Mounting Lip Diameter:** 1.8120 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Maximum Starting Torque:** 2.30 inch-ounces **Maximum Running Torque:** 1.80 inch-ounces **Shaft End Play:** 0.003 inches **Shaft Runout:** 0.0005 inches **Pilot Diameter Runout:**

0.0005 inches

NSN 5905-00-903-9675

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:

0.0005 inches

Mechanical Backlash In Deg Angular Rotation:

0.05

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

30.0 percent, rated amperes c and better select

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

1800.0 all sections

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

130.0 all sections

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections terminal base linearity

Fixed Tap Quantity Per Section:

1 all sections

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation all sections

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections graph

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Test Data Document:

06481-900056-10 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5905-00-903-9675

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0