Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-904-0366

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

### **Reliability Indicator:**

Not established

### Terminal Length:

0.538 inches

#### Mounting Hole Diameter:

0.093 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.062 inches

#### Body Length:

### 1.250 inches

**Body Width:** 

0.250 inches

Body Height:

0.359 inches

#### Shaft Style:

Round, slotted

Actuator Type:

Single shaft

### Center To Center Distance Between Terminals:

0.700 inches

**Fragility Factor:** 

Moderately rugged

### Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

# **Terminal Location:**

Lower adjacent side two rows

# Mounting Method:

Unthreaded hole

# Center To Center Distance Between Terminal Rows:

0.047 inches

# **Electrical Resistance Per Section:**

250.0 ohms single section

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches



**Power Dissipation Rating Per Section In Watts:** 

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0