NSN 5905-00-904-0483

Nonprecision Wire Wound Variable Resistor - Page 1 of 3

View Online at https://aerobasegroup.com/nsn/5905-00-904-0483



Section Quantity: Body Style: Cylindrical servo mounted **Pilot Diameter:** Between 0.62400 inches and 0.62500 inches Pilot Length: 0.06200 inches **Overall Length:** Between 2.239 inches and 2.269 inches **Terminal Length:** 0.250 inches First Flat Length: 0.560 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** Between 0.645 inches and 0.675 inches **Body Length:** 1.594 inches **Overall Diameter:** 1.062 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round, v flatted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 3620.0 **Maximum Starting Torque:** 1.00 inch-ounces

NSN 5905-00-904-0483

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Maximum Running Torque:
0.80 inch-ounces
Maximum Stop Torque:
100.00 inch-ounces
Shaft End Play:
0.00200 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.5
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3620.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Single section linear

NSN 5905-00-904-0483

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0