NSN 5905-00-904-3105

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-904-3105

Electrical Resistance: 2010.000 ohms Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches
Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Wire lead Reliability Indicator: Not established Body Diameter:
Reliability Indicator: Not established Body Diameter:
Not established Body Diameter:
Body Diameter:
0.336 inches
Body Length:
0.728 inches
Power Dissipation Rating In Watts:
2.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-22684/4 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0