## NSN 5905-00-904-4297

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-904-4297 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.063 inches **Shaft Diameter:** 0.050 inches **Shaft Length:** 0.035 inches **Body Length:** 0.375 inches **Body Width:** 0.150 inches **Body Height:** 0.375 inches Shaft Style: Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 0.419 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 20.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

## NSN 5905-00-904-4297

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No