NSN 5905-00-904-4359

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-904-4359

view Online at https://aerobasegroup.com/nsi//2905-00-904-4559
Section Quantity:
1
Body Style:
Rectangular w/mounting hole/slot
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.074 inches
Shaft Diameter:
Between 0.080 inches and 0.100 inches
Shaft Length:
Between 0.030 inches and 0.050 inches
Body Length:
Between 0.359 inches and 0.391 inches
Body Width:
Between 0.187 inches and 0.219 inches
Body Height:
Between 0.359 inches and 0.391 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Mounting Facility Quantity:
1
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-80.0/+80.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
FO/JEO gingle costion

-5.0/+5.0 single section

NSN 5905-00-904-4359

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: