

View Online at <https://aerobasegroup.com/nsn/5905-00-904-4371>

**Section Quantity:**

1

**Reliability Indicator:**

Not established

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.500 inches

**Shaft Style:**

Round

**Switch Type:**

Push-pull

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.437 inches

**Switch Operating Position:**

Any position of rotation travel

**Switch Contact Arrangement:**

Double pole, double throw

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

50.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Switch Current Type And Rating In Amps:**

0.500 ac/dc

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

6 solder stud and 3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0