

View Online at <https://aerobasegroup.com/nsn/5905-00-904-7024>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.6250 inches

Pilot Length:

0.0620 inches

First Flat Length:

0.250 inches

Flat Height:

0.093 inches

Undercut Diameter:

0.625 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.438 inches

Body Length:

1.625 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3580.0

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

1.20 inch-ounces

Maximum Stop Torque:

160.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.035/+0.035 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0