Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-904-7051

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes

## **Reliability Indicator:**

Not established

### Mounting Hole Diameter:

0.063 inches

#### Shaft Diameter:

0.050 inches

- Shaft Length:
- 0.035 inches

Body Length:

### 0.375 inches

Body Width:

# 0.150 inches

**Body Height:** 

0.375 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

### Lateral Distance Between Mounting Hole Centers:

0.419 inches

### **Mounting Facility Quantity:**

2

### Terminal Location:

Radially positioned over less than half the circumference

### **Mounting Method:**

Unthreaded hole

### **Electrical Resistance Per Section:**

1.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

9000.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section



### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

### Actuator Travel Control Feature:

Clutch

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0