Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-904-7691

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.672 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.438 inches

Mounting Bushing Length:

0.375 inches

#### Body Length:

# 0.312 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Locking bushing

#### **Electrical Resistance Per Section:**

200.0 ohms single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

#### Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0