## NSN 5905-00-904-8480

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-904-8480

Section Quantity:
2
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
5.1 55 1.15.1.55
Shaft Style: Round
Switch Type:
Push-pull
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.437 inches
Switch Contact Arrangement:
Double pole, double throw
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
500.0 percent, rated amperes c and better finish
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 1st section
Switch Current Type And Rating In Amps:
0.500 ac/dc
Standard Taper Curve Per Section:
·
A single section

## NSN 5905-00-904-8480

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity	Terminal	<b>Type</b>	And	Quantity	<b>/</b> :
----------------------------	----------	-------------	-----	----------	------------

6 solder stud and 3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0