NSN 5905-00-904-8505

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-904-8505

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.061 inches
Body Diameter:
0.656 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.562 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.500 inches
Overall Diameter:
1.188 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.234 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
Electrical Registance I & Occiton.

100.0 kilohms single section

NSN 5905-00-904-8505

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	Ambient Tempurature	In Deg	Celsius Pe	r Section	At Zero	Percent	Rated	Power:
--	---------------------	--------	-------------------	-----------	---------	---------	-------	--------

105.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0