NSN 5905-00-905-0339

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-905-0339 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.375 inches **Body Length:** 0.422 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Terminal Location:** Rear end **Mounting Method:** Tab **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 1.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** 275.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

Unit Of Measure:

NSN 5905-00-905-0339

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| _ | | | | | | |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | tor | 172 | + 1 | nn | |
| | | | | | | |

No

Fiig:

A002a0