

View Online at <https://aerobasegroup.com/nsn/5905-00-905-0495>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

First Flat Length:

0.187 inches

Flat Height:

0.245 inches

Body Diameter:

0.938 inches

Shaft Diameter:

0.375 inches

Shaft Length:

0.562 inches

Mounting Bushing Length:

0.313 inches

Body Length:

0.875 inches

Undercut Diameter:

0.250 inches

Shaft Style:

Round, slotted

Actuator Type:

Dual concentric

Maximum Starting Torque:

20.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Undercut Length:

0.250 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

250.000 ohms c and better industrial clears

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0