NSN 5905-00-905-1047

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-905-1047 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 3.527 inches **Undercut Diameter:** 1.870 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.609 inches and 0.641 inches **Body Length:** Between 2.590 inches and 2.652 inches **Overall Diameter:** 2.000 inches **Mounting Lip Diameter:** Between 2.0000 inches and 2.0050 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:**

Maximum Starting Torque

1.80 inch-ounces

Maximum Running Torque:

1.40 inch-ounces

NSN 5905-00-905-1047

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
600.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.0005 inches
Lateral Runout:
0.0015 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Rear end
Mounting Method:
Servo mount
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
540.0 single section
Rotary Actuator Travel In Angular Deg:
1260.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
4.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
1000.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

NSN 5905-00-905-1047

Precision Wire Wound Variable Resistor - Page 3 of 3



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0